

Grapho-Glas[®] Gasketing

Item 90, 91, 91N, 92, 92W, 94, 720, 721,
721N, 722, 723, 724, 725, 726

- Black fiberglass gasketing
- Graphite impregnated
- Braided to resist unwinding
- Available in many sizes and lengths



Description:

Grapho-Glas is used as gaskets on the doors of wood burning stoves. They are graphite impregnated to resist abrasion and last longer. Grapho-Glas is used as original equipment by major stove manufacturers as well a replacement for worn out gaskets. Available in many sizes and lengths.

Performance Characteristics:

- Abrasion resistant
- Blends in with the stove
- Resists creosote adhering to it
- Withstands temperatures up to 1000°F

Recommended Uses:

Used as original equipment by stove manufacturers and as replacement gasketing for wood burning stoves, coal stoves, and fireplace insert stoves.

Application:

Follow directions provided with Rutland Stove & Gasket Cement.

Typical Physical Properties:

Service Temperature	1000°F
Consistency	Fibrous
Flashpoint	N/A
Color	Black
Storage/Handling	Use gloves when handling

Limitations:

Not recommended to come in contact with food.

Warranty and Limited Remedy:

This product will be free from defects in material and manufacture for a period of eighteen (18) months from date of manufacture. Rutland Fire Clay Company makes no other warranties including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the Rutland Fire Clay Company product is fit for a particular purpose and suitable for user's application. If this Rutland Fire Clay Company product is defective within the warranty period stated above, your exclusive remedy and Rutland Fire Clay Company's sole obligation shall be, at Rutland Fire Clay Company's option, to replace the Rutland Fire Clay Company product or refund the purchase price of the Rutland Fire Clay Company product.

Limitation of Liability:

Except where prohibited by law, Rutland Fire Clay Company will not be liable for any loss or damage arising from this Rutland Fire Clay Company product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

CAUTIONS:

Fiberglass can cause irritation to skin, respiratory tract and eyes. If skin contact, wash with soap and water. If inhaled, move to fresh air. If cough or other symptoms develop, get

medical attention. If contact with eyes, flush with water for at least 15 minutes. Consult physician.

**KEEP OUT OF REACH OF CHILDREN
EYE, SKIN, AND RESPIRATORY TRACT
IRRITANT**

Technical Data on the EZ Spread Fiberglass Cement is found on that product page.